

SAFETY DATA SHEET

conforms to Regulation (EC) No. 1907/2006

1 IDENTIFICATION OF THE PRODUCT AND THE COMPANY

- 1.1. **Product:** Cobra Picture Varnish satin (Aerosol) 400ml
Art. no.: 9516.3118
- 1.2. **Company:** Royal Talens
Sophialaan 46, 7311 PD, Apeldoorn, the Netherlands
P.O. Box 4, 7300 AA, Apeldoorn, the Netherlands
Telephone +31 (0)55 - 5274700
Telefax +31 (0)55 - 5215286
www.talens.com
info@talens.com

2 HAZARDS IDENTIFICATION

Extremely flammable.
For more information see 15.

3 COMPOSITION AND INFORMATION ON INGREDIENTS

Dangerous components:	Naphtha(petroleum), heavy alkylate	Propane	Butane
% by weight:	25-50	10-25	10-25
CAS-no.:	64741-65-7	74-98-6	106-97-8
EINECS-no.:	265-067-2	200-827-9	203-448-7
Symbols:	Xn	F+	F+
R-phases:	53,65,66	12	12

4 FIRST-AID MEASURES

- Inhalation:** Move to fresh air.
- Skin contact:** Wash affected areas with soap and water.
Remove contaminated clothing.
- Eye contact:** Flush immediately with large amounts of water for 15 minutes. Consult a physician.
- Ingestion:** Drink one or two glasses of water to dilute. Do not induce vomiting. Consult a physician.

5 FIRE-FIGHTING MEASURES

Suitable: foam, CO2, dry chemical. Water should be used to cool containers, exposed to fire.

6 ACCIDENTAL RELEASE MEASURES

Provide sufficient ventilation. Remove all sources of ignition. Absorb on a suitable substrate.

7 HANDLING AND STORAGE

Use only in well ventilated areas. Store containers out of sun and away from heat, sparks and flame.

8 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Provide sufficient ventilation to keep vapourconcentration low. Use protective gloves in case of prolonged or repeated contact. Wash hands before eating, drinking or smoking.

9 PHYSICAL AND CHEMICAL PROPERTIES

Characterization:	Synthetic resin in hydrocarbon solvent		
Form:	Spraycan		
Odour:			
pH:	n.a.	(20°C)	
Viscosity:		mPa.s (20°C)	
Boilingpoint/-range*:	- 44		°C
Meltingpoint/-range*:			°C
Flashpoint*:	- 97		°C
Ignitiontemperature*:	354		°C
Explosionlimits*:	lower: 0.7 vol %; upper: 10.9 vol %		
Vapourpressure*:	approx. 8300		mbar (20°C)
Density*:	0.68		g/cm ³ (20°C)
Solubility in water*:	insoluble		g/l

10 STABILITY AND REACTIVITY

N.a.

11 TOXICOLOGICAL INFORMATION

Acute toxicity:

64741-65-7 Naphta (petroleum), heavy alkylate

Oral	LD50	>6000mg/kg (rat)
Dermal	LD50	>3000 mg/kg (rat)
Inhalation	LC50/4h.	> 7,8 mg/l (rat)

12 ECOLOGICAL INFORMATION

This product contains no CFC propellant.

13 DISPOSAL CONSIDERATIONS

Comply with local regulations.

14 TRANSPORT INFORMATION

UN-no.: 1950
 Land ADR/RID: 2, 5F
 Water ADNR:
 Sea IMDG: 2.1
 Air ICAO/IATA-DGR: 2.1
 Packing group: -
 Other information:

15 REGULATORY INFORMATION

Labelling in accordance with directive 1999/45/EC and Regulation (EC) No. 1272/2008

Classification Extremely flammable



Symbol

Risk phrase

R12 – Extremely flammable
 R53 – May cause long-term adverse effects in the aquatic environment
 R66 – Repeated exposure may cause skin dryness or cracking

Safety phrase

S2 – Keep out of reach of children
 S23 – Do not breathe vapours
 S24 – Avoid contact with skin
 S51 – Use only in well-ventilated areas

Other phrases

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

16 OTHER INFORMATION